FND 法诺德

FND-PQ200 High Pressure Thermic Lance

Core Technology & Extraordinary quality



Product Introduction



The FND-PQ200 high-pressure hot air gun is mainly used for reheating asphalt pavement, dehumidifying cracks, and cleaning. Its unique design makes construction safer, more reliable, and more efficient.

Working principle:
The engine drives the compressor to produce high-pressure gas, and liquefied gas is mixed with compressed air in the combustion chamber of the thermal spray gun to produce high-temperature gas for construction use.

Basic Overview



Technical Parameter

Model specifications		FND-PQ200
Overall dimensions		1750X680X1080
Net weight		150KG
Engine part	Engine	
	Starting method	
	Oil capacity	1.1L
	Fuel tank capacity	6L
Compressor	Power	6.5ps
	Rated exhaust capacity	0.55m³/min
	Rated pressure	0.8Mpa
Air storage tank	Volume	70L
	Rated pressure	1.0Mpa
	Safety valve	Dual pressure relief valve, dual protection
Extend trachea		10M

Product Display



FND 法诺德
E-mail：wangxumin@fanuode.cn
SuZhou FaNuoDe Engineering Machinery Co.,Ltd.

Address：No. 25 Tongxin West Road, Hengfan Street, Wujiang District, Suzhou City, Jiangsu Province
TEL: 0512-62538115/+86 13771800605